

Package: rpublons (via r-universe)

May 8, 2026

Type Package

Title Client for Publons.com

Version 0.1.1

Date 2017-05-18

Description Extract review information information from Publons
<<https://publons.com>>.

License MIT + file LICENSE

URL <https://github.com/leeper/rpublons>

BugReports <https://github.com/leeper/rpublons/issues>

Imports htr, magrittr, jsonlite, tidyr

Suggests testthat

RoxygenNote 7.1.2

Config/pak/sysreqs libicu-dev libssl-dev

Repository <https://favstats.r-universe.dev>

Date/Publication 2022-03-04 18:28:15 UTC

RemoteUrl <https://github.com/favstats/rpublons>

RemoteRef HEAD

RemoteSha b3a942be32989e6f6f94abe7f6b3b8a17df00ff3

Contents

rpublons-package	2
Index	4

rpublons-package *rpublons*

Description

Client for Publons.com

Usage

```
publons(  
  verb = c("GET", "POST", "HEAD", "OPTIONS"),  
  endpoint,  
  body = NULL,  
  query = NULL,  
  researcher_id = NULL,  
  ...,  
  base_url = "https://publons.com/api/v2/",  
  token = Sys.getenv("PUBLONS_TOKEN"),  
  username = Sys.getenv("PUBLONS_USERNAME"),  
  password = Sys.getenv("PUBLONS_PASSWORD")  
)  
  
publons_auth()
```

Arguments

verb	A character string containing an HTTP request verb.
endpoint	A character string containing an API endpoint.
body	Optionally, a request body.
query	Optionally, a list containing HTTP query arguments.
base_url	A character string specifying the base URL for the API.
token	A character string containing a Publons API token. By default, taken from environment variables.
username	A character string, containing a Publons username, passed to <code>publons_auth</code> if token is missing. This is used to generate an API token, if needed.
password	A character string, containing a Publons password, passed to <code>publons_auth</code> if token is missing. This is used to generate an API token, if needed.

Details

Extract review information information from Publons <https://publons.com>. This is currently a low-level client that handles authorization but no high-level functionality.

Author(s)

Thomas J. Leeper <thosjleeper@gmail.com>

References

[Publons API v2 Documentation](#)

Examples

```
## Not run:
# retrieve and store API token
publons_auth("myusername", "mypassword")

# get list of academics
publons("GET", "academic/")

# get academics by institution
publons("GET", "academic/", query = list(institution = "Harvard University"))

# get a specific academic by ORCID
publons("GET", paste0("academic/", "0000-0003-4097-6326"))

# get reviews for a specific academic by ORCID
publons("GET", "academic/review/",
        query = list(academic = "0000-0003-4097-6326"))

# get a specific review
publons("GET", paste0("academic/review/", "YK8zafgo"))

## End(Not run)
```

Index

* **package**

rpublons-package, [2](#)

publons (rpublons-package), [2](#)

publons_auth (rpublons-package), [2](#)

rpublons (rpublons-package), [2](#)

rpublons-package, [2](#)